

DECLARATION OF PERFORMANCE

No.GEO.005CPR2013-07-01

1. Unique identification code of the product type Type, batch or serial number or any other element allowing identification of the product Dry-pressed ceramic tiles, with low water absorption $E_b \le 0.5 \%$ with thickness < 7.5 mm

2. Intended use(s)

For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

GEOTILES, S.L.U.

Carretera Vila-real - Onda, Km 6 12540 Vila-real (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

5. Name and identification number of notified laboratory, if relevant - not applicable Task(s) carried out **AVCP** system Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	
Release of dangerous substance, for:		
- Cadmium	< 0,01 mg/l	
- Lead	< 0,1 mg/l	
Breaking strength	> 700 N	
Slipperiness	NPD	
Tactility	NPD	EN 14411:2012
Bond strength/adhesion, for:		
Cementitious adhesive, type C2 E S2	> 1 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Pedro Vilar (Manager

Name and function

Cira. Vila-real - Onda, Km. 12540 VILA-REAL (Costellon) ESPAÑA Signature

Vila-real, 01-01-2023

Place and date of issue